



PIN	1	2	3	4	5	6	7	8	9	10	11
CONNECTION	FG	VSS	VDD	V0	Vout	/WR	/RD	/CE	C/D	HALT	RST
PIN	12	13	14	15	16	17	18	19	20	21	22
CONNECTION	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	NC	BLA	BLK

Specification:

- 1). Driving: Duty: 1/128, Bias:1/12, VLCD:13.6V, VDD:5.0V
- 2). Viewing angle: 6 0'clock
- 3). Display mode: STN/Negative/Transmissive/Blue
- 4). Operating temp.: -20°C~+70°C
Storage temp.: -30°C~+80°C
- 5). Control IC: T6963C (or compatible)
- 6). Backlight: Edge White
- 7). Dimensions with mark "()" are important, with mark "*" are referenced
- 8). All the raw materials are RoHS compliant

REV	REVISION RECORD	DATE
A0	First issue	03/14


 深圳市三元晶科技有限公司
 Shenzhen TCC LCD Hi-Tech Co., Ltd.

MODEL NO. 模组型号	SYM160128A1V13-5C5BLN7R8-B5N1			GENERAL TOL: ±0.3
APPROVED BY	CHECKED BY	DRAWING BY	PAGE: 1 OF 1	UNIT: mm
			页面	单位
			投影	三角法